

TEKNO/1SN

EN 853 1SN - SAE 100 R1AT

Operating temperature range: -40°C +100°C

Qualified fluids: Mineral oils, glyco & polyglycol based oils, synthetic ester based oils, water

Tube: Oil resistant synthetic rubber

Reinforcement: one high tensile steel braid

Cover: black, oil and environment resistant synthetic rubber

Maker: **Vitillo S.p.a - Italy**



Item	Model	Ware braid	Dimensions (mm)				Pressure		Weight kg/mt	Part of Ferrule	Unit price VND/Mt
			I.D (inch)	I.D	O.D	Bending	W.P	B.P			
1	TH1SN04	1	1/4"	6,4	13,1	100	225	900	0,230	B12T04N	
3	TH1SN06	1	3/8"	9,5	17,1	130	180	720	0,360	B12T06N	
4	TH1SN08	1	1/2"	12,8	20,2	180	160	640	0,430	B12T08N	
5	TH1SN10	1	5/8"	16,0	23,4	200	130	520	0,510	B12T10N	
6	TH1SN12	1	3/4"	19,0	27,4	240	105	420	0,620	B12T12N	
7	TH1SN16	1	1"	25,4	35,3	300	88	352	0,935	B12T16N	
8	TH1SN20	1	1.1/4"	31,8	42,9	420	63	252	1,300	B12T20N	
9	TH1SN24	1	1.1/2"	38,1	50,1	500	50	200	1,550	B12T24N	
10	TH1SN32	1	2"	50,8	63,4	630	40	160	2,300	B12T32N	